

Seismic Handler installation

Seismic Handler is only available for Linux systems. Support for other Unix operating systems was dropped. Installation instructions listed here are only valid for the latest software release.

Preparation

On this site only the source code of Seismic Handler is available. In order to compile it please install all necessary software for X11 and Motif development. Detailed instructions are available for following Linux flavours:

- [Ubuntu](#) and related systems like Kubuntu, Xubuntu, ...
- [openSUSE](#)
- [Debian](#)
- [Fedora](#) (complex installation)

Download

Download the latest installation package: [?SHM-20112-install.sh](#) (also see [release notes](#)).

If you plan to install SH/SHM at a system without internet access, please also download the FK and LocSAT archives. If an internet connection is available at the target system, these files will be downloaded **automatically**:

- [?FK package](#) (only necessary if no internet connection available at target system!)
- [?LocSAT](#) (ditto)

Installation

1. Start installation in the directory you downloaded the installation package:

```
$ bash ./SHM-20112-install.sh
```

If you need to use alternative locations for LocSAT/FK simply add them as parameter, for example like

```
$ bash ./SHM-20112-install.sh -l /tmp/locsat-linux.tar.gz -f /tmp/fk-linux.tar.gz
```

Please always use absolute pathnames! It's also possible to use an FTP or HTTP address, e.g: -l http://localmirror/locsat-linux.tar.gz.

2. If you have no administrative rights, you can perform an user installation to any directory you are able to write in.
3. LocSAT and fk are downloaded from our FTP server automatically. If you set alternate locations, these will be used.
4. Before performing the installation, you can alter some automatically detected settings:

```
(u) user root path:          $HOME/shfiles
(e) window based texteditor: kwrite
(c) linux colors:           yes
```

- If everything is ok, start compiling by typing "i".
5. Compilation process takes place. Please look for compiling errors.
 6. Finished. If any problems are found, the temporary directory with the installation sources is kept, otherwise deleted.
 7. Update your environment depending on your shell (edit ~/.cshrc or ~/.bashrc respectively). The exact procedure depends on the installation path. After installing SH/SHM the setup routine will display the effective information.

If you have problems installing SH/SHM please contact us via discussion forum or [?users mailing list!](#)

If you are new to Seismic Handler To continue please read the [instructions for the first steps](#) after installation.

Known issues

- If you installed SH/SHM as root user, you may need to update the ownership of ~/shfiles:

```
cd ; (sudo) chown -R $USER shfiles
```

- On KDE systems there's a short pause after start-up of SHM.
- [Issues that apply to Ubuntu only](#)
- [Issues that apply to openSUSE only](#)
- [Issues that apply to Debian only](#)